

All rights reserved. Any disclosure or reproduction to a third person is submitted to an authorization.

DEFINITION	4 lug cap for vacuum sealing on threaded ring with the following designation:		NF EN ISO 9100-8 03-2005 /GME 20-06 (GPI 2030)								
PROFILED PANEL	RTS Regular Twist off with Step / RTS										
SIZES	Please refer to drawing ET63H10RTS at the bottom of the page.										
METAL	Category: tin steel Thickness: 0,15 mm Tinning: 2.8/2.8 g/m² All the metal characteristics comply to the European standard EN 10202										
COMPOUND (P27)	Food contact compound PVC ESBO suitable for non-fatty products and pasteurisation heat treatments up to 100°C. Nominal compound thickness 0.8 mm +/- 0.20 mm										
INTERIOR PROTECTION (2WHPN)	For fairly corrosive and corrosive products: 1 operation of base coat BPA NI and PFAS NI + 1 operation of white organosol varnish BPA NI and PFAS NI										
PROTECTION AND EXTERIOR DECORATION	VARNISH WHITE+CLEAR										
DECLARATION OF CONFORMITY	Please refer to declarations of conformity										
PACKAGING (weights are given with ± 10%)	Average weight of a cap: 7,8 g Gross average weight of a carton: 11,7 kg Number of caps/carton: 1400 (in plastic bags)										
	<table><tr><th>Number of cartons / pallet</th><th>Number of caps / pallet</th><th>Gross average weight</th><th>Pallet size</th></tr><tr><td>30</td><td>42000</td><td>351</td><td>800 X 1 200 X 2 220 mm</td></tr></table>			Number of cartons / pallet	Number of caps / pallet	Gross average weight	Pallet size	30	42000	351	800 X 1 200 X 2 220 mm
Number of cartons / pallet	Number of caps / pallet	Gross average weight	Pallet size								
30	42000	351	800 X 1 200 X 2 220 mm								
STORAGE CONDITIONS AND DLUO	Please refer to Caps user guide for the Massilly group		regarding storage								
USE CONDITIONS	Please refer to Caps user guide for the Massilly group		regarding caps and their relevant use.								
DRAWING ET63H10RTS											